

TOP Flauto

| | |
|-------------------------------|---|
| Type: | Fullrange |
| Components: | 8 x 3" fullrange driver |
| Power: | 350W RMS |
| Frequency Range: | 140Hz-20KHz |
| Sensitivity: | 100dB 1W 1m |
| Nominal Dispersion (-3dB): | Horiz. 120° Vert.15° |
| Nominal Impedence: | 4Ω |
| Forniture: | Wood front loading |
| Suspension system: | 6 points with M8 thread |
| Mechanical Protection System: | Metal grid |
| Connection: | 1 Neutrik Speakon NL4MP R |
| Color: | Scratchproof black paint or customized on request |
| Dimensions: | 145 x 120 x 680 mm (W,D,H) |
| Weight: | 7,2 Kg |



The FLAUTO loudspeaker is dedicated to all kind of use like meetings, live concert and parties with Djs because it has an high quality performance with high SPL energy. The FLAUTO loudspeaker is based on array design for vertical connections so its vertical dispersion is very close to not generate noise between the various modules, while in horizontal manages to cover a radius of 120°.

The choice of using paper fullrange components is designed to have a tone as natural as possible without that listening fatigue of traditional professional systems.

Another important detail is the furniture making, wooden and very rigid with a horn loading on the front for modulating the dispersion and increase the efficiency.

The efficiency of FLAUTO loudspeaker is amazing especially as they can play on long distances keeping their performance.